

AP-Series Label Applicators



AP 362e
LABEL APPLICATOR



Primera's AP-Series Label Applicators are the perfect semi-automatic labeling solution for cylindrical containers as well as many tapered containers, including bottles, cans, jars and tubes.

Set-up and operation is fast and easy. Just:

1. Set the guides
2. Place your container in the machine
3. Press the footswitch and your label is applied

The built-in spring-loaded pressure arm makes sure labels are applied firmly and without wrinkles.

With an AP-Series Label Applicator you'll apply labels faster and more accurately – helping to speed up your production and sell more of your products!



PRIMERA
TECHNOLOGY, INC.

Apply Labels Fast and Accurately

With an AP-Series Label Applicator you'll be able to apply labels at speeds of up to 1200 per hour. Labels are perfectly applied without wrinkles, giving your finished products a highly professional look.

AP-Series Label Applicators are an ideal accessory to Primera's LX- or CX-Series label printers. The applicators can also apply roll-fed, pressure-sensitive labels produced by most other flexographic, offset and digital presses.

Two Models Available



AP360e is the base model. It quickly and efficiently applies single labels at a time.



AP362e is an advanced model. It can apply one or two different labels to a single container. A built-in LED counter and memory for up to nine front-to-back label offsets is also included.

Features

- » Quick set-up and easy operation
- » Accurately applies labels to the front (AP360e) or front and back (AP362e) with variable spacing
- » Fast – labels are applied at 135mm (5.3") per second – up to 1200 containers per hour
- » Compact size – fits on most desks and countertops
- » Professionally designed – one of the only semi-automatic label applicators available with UL, CSA and FCC safety and emissions certifications
- » Industrial strength – built with heavy-duty sheet metal and steel for long life

Specifications

Container Width:	25.4mm to 238mm (1" to 9.4")
Container Diameter:	15mm to 170mm (0.6" to 6.7")
Container Shape:	Cylindrical and many tapered
Supply roll diameter:	Up to 203mm (8")
Media liner width:	25.4mm to 213mm (1" to 8.375")
Supply roll core:	51.8mm to 76.2mm (2" to 3" I.D.)
Electrical rating:	12VDC, 5.0A
Power requirements:	100-240VAC, 50/60 Hz, 60 watts
Agency certifications:	UL, UL-C, CE, FCC Class A
Weight:	7.26 kg
Dimensions:	340mmW x 226mmH x 328mmD
Gap between Labels:	Recommended: 3.175mm – 6.350mm (1/8" – 1/4")
Label Type:	Die cut with waste removed. Clear labels can be used
Liner Thickness:	2 mil – 10mil (smoothness will affect feeding – a liner that is too slippery or too thin will slip through the drive rollers)
Label + Adhesive Thickness:	5 mil – 15mil *
Wind Direction:	Wound out

* Important Note: Pliability/Flexibility/Rigidity of the label is also a factor. If the label is too flexible, no matter the thickness, it can cause wrinkling or it may not pop off the liner when going around the peel edge. Polypropylene, Polyester and Vinyl labels tend to be more flexible than paper labels. If you suspect the label stock is too flexible, it is recommended that the stock and container be tested on the Applicator before making any purchase decisions of label stock or the applicator.



AP-Series Label Applicators are the perfect accessory to Primera's LX500e and LX1000e/LX2000e Color Label Printers

PRIMERA
TECHNOLOGY EUROPE™
Mainzer Strasse 131
65187 Wiesbaden / Germany
Fon: +49 (0) 611 - 92777-0
Fax: +49 (0) 611 - 92777-50
<http://primeralabel.eu>
<http://primera.eu>
E-mail: sales@primera.eu