



# RW-7

## LABEL REWINDER

\*LX2000e printer sold separately



**PRIMERA**  
TECHNOLOGY EUROPE™  
primeralabel.eu

## No more self-rewinding of labels

Primera's UW-7 Label Unwinder and RW-7 Label Rewinder make it easy to unwind and rewind large quantities of labels.

They're perfect for use with virtually any thermal, thermal transfer and inkjet-based desktop label printer, including Primera's popular LX500e and LX2000e colour label printers.

The RW-7 rewinds the rolls perfectly tight and straight, there's no need to rewind it properly by hand.

Load up to an 203.2mm (8") roll to increase your unwind capacity by two times. Tape the printed output onto a 76.2mm (3") core. Drop the dancer arm and start printing. Your labels will be rewound with perfect alignment and just the right amount of tension for either hand application or on a semi-automatic or automatic label applicator.

UW-7 and RW-7 are sold separately since some people may only want to rewind. Together, they make it fast and easy to produce higher volumes of professional-grade label rolls.


## Rewinding Directions



Label Inside




Label Outside



**Note:** Using the UW-7 with the LX900e Color Label Printer requires modification in operating the unit. Please contact us for further information.

## Features

- Light-weight dancer arm – for use with virtually any desktop label printer
- Coloured LED indicator provides rewinder operation status



- Gummed dancer arm attracts dust and keeps it away from the label surface
- Won't cause alignment or print quality problems
- Universal Power Supply – simply change cord set for use in any country
- Modular core adaptor fits 1", 1.5", 2" and 3" core sizes
- Easy assembly lock module for quick and firmly label roll holding

## Specifications

<b>Maximum Roll Width:</b>	178mm (7")
<b>Maximum Roll Diameter:</b>	153mm (6")
<b>Rewind Speed:</b>	Auto mode: 30.48cm/sec (12"/sec) Fixed mode: Coreless 13.71cm/sec (5.4"/sec) 1" core diameter 16cm/sec (6.3"/sec)
<b>Core Size:</b>	Coreless, 25.4mm (1"), 38.1mm x 50.8mm (1.5x2"), 76.2mm (3")
<b>Label Roll Weight:</b>	5 kg (11 lbs.)
<b>Rewinding:</b>	Label Inside/Label Outside
<b>Power Input:</b>	100-240VAC to 24 VDC, 2A, 50/60 Hz
<b>Weight:</b>	5 kg (11 lbs.)
<b>Dimensions:</b>	394mmW x 303mmH x 180mmD (15.51"W x 11.93"H x 7.08"D)
<b>Storage Temperature:</b>	-20°C to 60°C (-4°F to 122°F)
<b>Humidity:</b>	10% - 85% non-condensing
<b>Certifications:</b>	CE, RoHS, TÜV, FCC
<b>RW-7 Compatibility:</b>	Works with LX400e, LX500e, LX900e* and LX2000e *(LX900e requires label stock greater than or equal to 4 inches in width)
<b>UW-7 Compatibility:</b>	Works with LX400e, LX500e and LX2000e
<b>Warranty:</b>	Two years (Second year must be obtained by product registration)

**Important Note:** Pliability/Flexibility/Rigidity of the label is an important factor for the smooth transport of the label rolls in the rewinder. If the label is too flexible, no matter the thickness, it can cause uneven winding, slipping, or stopping of the rewinder. Polypropylene, Polyester and Vinyl labels tend to be more flexible than paper labels. If you suspect the label stock is too flexible, it is recommended that the stock is tested on the rewinder before making any purchase decisions of label stock or the rewinder. Original Primera substrates do not slip or cause any damage.

**FOR MORE INFO,  
VISIT US AT [PRIMERALABEL.EU](http://PRIMERALABEL.EU)**

**PRIMERA**  
TECHNOLOGY EUROPE™

Mainzer Strasse 131  
65187 Wiesbaden/Germany  
Fon: +49 (0) 611 - 92777-0  
Fax: +49 (0) 611 - 92777-50  
<http://primeralabel.eu>  
Email: [sales@primera.eu](mailto:sales@primera.eu)